



List of parts

Title	Number
① Gasket, PUR or HE/CR	2
② Cover, PA	1
③ Outer straps, PES	4
④ Pleated media	1
⑤ Bottom, PS	1

Necessary accessories:

Reusable support cage 145/1000

Optional: Pulse-jet-deflector PJR 145

Type **LP 145 G 10 A 27 06**

Filter medium:	FE 2506-01-sine, PES (antistatic)	Filter surface:	2.7 [m ²]
Number of pleats:	54	Height of cartridge H:	1005 [mm]
		Depth of pleats:	25 [mm]

Filter cartridges for dust removal according to our separate application guidelines

- **Antistatic cartridge:** The user has to ground the cartridge versus the filter housing by metallic contact between the cartridge cover and the mounting plate.
- For mounting from upstream- or downstream-side.
- Recommended **diameter for mounting** down-stream-side: **147 mm**.
- Distance spacers of the cover to optimize the compression of the gasket
- Centering ring of the cover to protect the filter media from damage.
- Filter media fulfils dust class M according to DIN EN 60335-2-69 annex AA.

The values given are mean values with tolerances resulting from normal production fluctuations.
Our explicit written confirmation is always required for the correctness and applicability of the particulars involved in any individual case.
All preceding versions are hereby rendered invalid.

Issued: Feb 2005/JK